

# ENOC SPIRO PA

## PRODUCT DESCRIPTION

**ENOC SPIRO PA oils** are a range of high performance polyalphaolefins (PAO) based synthetic compressor lubricants giving the very best performance in rotary flooded air compressors to provide long service life in extreme operating conditions.

## APPLICATIONS

- ◆ Rotary oil-flooded screw and vane compressors
- ◆ Compressors operating in extreme ambient conditions
- ◆ Two stage Compressors operating at high pressures and temperatures
- ◆ Critical compressor applications where long life oil life, and high performance operations are required

## PERFORMANCE STANDARDS

NF-ISO 6743 DAJ

***Always follow the compressor manufacturer recommendations for required lubricant performance.***

## BENEFITS

### SPIRO PA provides:

- ◆ Optimisation of compressor efficiency
- ◆ Extended oil drain intervals up to 8000 hours with lubricant analysis monitoring
- ◆ Excellent resistance to carbon build-up
- ◆ Very high viscosity index to cover a wide temperature of operations
- ◆ Excellent low volatility characteristics to reduce oil consumption

Technical Data*				
ISO Grade	32	46	68	100
Density @ 15 °C	0.859	0.862	0.840	0.869
Viscosity , mm <sup>2</sup> /s @ 40°C	32	46	68	100
Viscosity Index	136	139	147	143
Flash Point, COC, °C	250	255	262	265
Pour Point, °C	-42	-42	-42	-39
Product code	245056	245057	245058	245059

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.