



ENOC CIRCULA

PRODUCT DESCRIPTION

ENOC CIRCULA are general purpose oils made from selected paraffinic base stocks. They have high viscosity indexes, and good natural water separating characteristics and are suitable for applications where straight mineral oils are acceptable for light duty lubrication.

APPLICATIONS

- ◆ General purpose industrial lubrication
- ◆ Once through total loss lubrication systems
- ◆ Light duty gear cases
- ◆ Engine air cleaners
- ◆ Chains and cables

PERFORMANCE STANDARDS

DIN 51506 VB-L

Always follow equipment manufacturers recommendations for required lubricant performance levels and viscosity grades.

BENEFITS

Circula provides:

- ◆ A wide range of viscosities
- ◆ High viscosity index
- ◆ Natural oxidation stability which helps to resist oil degradation
- ◆ Resistance to sludge formation
- ◆ Good natural water separation characteristics

Technical Data*								
ISO Grade	32	46	68	100	150	220	320	460
Viscosity								
mm ² /s @ 40°C	31	44	68	98	148	210	315	440
mm ² /s @ 100°C	5.2	7.0	9.0	10.7	15.3	18.9	25.0	29.8
Viscosity Index	100	98	97	96	96	96	96	96
Pour Point, °C	-9	-9	-9	-9	-9	-9	-9	-6
Flash Point, COC, °C	210	220	230	248	255	260	280	287
Product code	248002	248007	248001	248003	248004	248005	248006	248008

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.