

# ENOC ACTIVE PREMIUM

## PRODUCT DESCRIPTION

**ENOC ACTIVE PREMIUM** meets the specifications Dexron® III H and Ford Mercon® for automatic transmissions and power steering fluid. It is designed for the lubrication of torque converters, transmission gear and hydraulic systems used in passenger cars, light trucks and heavy vehicles. Active Premium is formulated to perform with exceptionally high technical standards needed to meet the wide range of lubrication requirements found in transmission systems requiring DexronIII/Mercon specifications.

## APPLICATIONS

- ◆ Car and light truck automatic transmissions
- ◆ Heavy duty truck automatic transmissions
- ◆ Off-highway plant equipment using full or semi automatic gearboxes
- ◆ Power steering where ATF Dexron® III H or Mercon® fluid is recommended
- ◆ Rotary air compressors requiring anti-wear type compressor oil
- ◆ Marine anti-wear hydraulic systems in low temperature applications
- ◆ Mobile equipment hydraulic systems

## PERFORMANCE STANDARDS

**ACTIVE PREMIUM** meets the following OEM and International specifications:

General Motors	DEXRON® III H fluid
Ford	MERCON® fluid
Allison	C-4

*Always follow equipment manufacturer's recommendation for required lubricant performance levels and oil drain intervals.*

## BENEFITS

**ACTIVE PREMIUM provides:**

- ◆ The latest automatic transmission fluid specifications
- ◆ Maximum transmission life through high performance chemical additive technology
- ◆ Smooth gear-changing through balanced anti-wear and friction modifier characteristics
- ◆ Compatibility with International Oil company competitor products
- ◆ Suitability for a wide range of applications which assist with inventory control

**Caution:** *Do not overfill automatic transmissions as this may cause foaming and possible malfunction of the unit.*

Technical Data*	
Colour	Red
Density @ 29.5 °C	0.8592
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	34.03
Kinematic Viscosity mm <sup>2</sup> /s @ 100°C	7.05
Dynamic Viscosity, mPa.s @ -40 °C	20,000 max.
Viscosity Index	176
Flash Point, °C	210
Pour Point, °C	-45
Product Code	221002

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.