



# ENOC EN MOULD GBO

## PRODUCT DESCRIPTION

**ENOC ENMOULD GBO** is very effective mold release or parting compounds for cast concrete products. It is formulated from highly refined mineral oils, produces a high quality stain and blemish free concrete finish with minimum incidence of blowholes giving clean uniform surface finish. **ENOC ENMOULD GBO** provides high level of corrosion protection to metal forms in use, storage and in transit. The oil contains barium and calcium.

## APPLICATIONS

- ◆ Supplied ready to use- no need to dilute product. Apply before first pour and re-apply before subsequent pours immediately after stripping and cleaning the mould.
- ◆ Application can be by spray or fine haired brush. Excessive application should be avoided; only a very thin coating should be applied.
- ◆ Spray application should only be with a nozzle giving a fine mist. Over application-ponding on horizontal surfaces can give surface retardation.

## BENEFITS

### ENOC ENMOULD GBO provides:

- ◆ Good performance in the prefabrication of aerated concrete with metal forms.
- ◆ Clean release even with porous materials
- ◆ High coverage, Water repellent; prevent rust
- ◆ Suitable for use with potable water structures

Technical Data*	
<b>ENOC ENMOULD GBO</b>	
Color	L5.0
Density @ 29.5 °C	0.892
Kinematic Viscosity @ 40°C	292
Kinematic Viscosity @ 100°C	22.70
Viscosity Index	96
Total Acid Number mg KOH/gm	4.91
Product Code	281001

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. **IT IS HARMFUL TO DRINK, KEEP AWAY FROM CHILDREN**