



ENOC EXERTA

PRODUCT DESCRIPTION

ENOC EXERTA oils have been developed to meet the special lubrication requirements of percussion type pneumatic tools working under arduous conditions. They are formulated from highly refined mineral oils providing a high film strength and incorporating EP, rust and corrosion inhibitors and tackiness additives to meet the demanding lubrication requirements of pneumatic drill impact.

APPLICATIONS

- ◆ Percussion type pneumatic drills including their use in rock drilling
- ◆ Jackhammers used in concrete and pavement breakers.
- ◆ Lubrication of air-line air tools
- ◆ Centralised lubricators used in large crawler-mounted drill rigs

PERFORMANCE STANDARDS

EXERTA meets and exceeds the following International specification:
ISO 6743/11 Class P

EXERTA viscosity grade should be selected according to the requirements of the application as specified by the equipment manufacturer.

BENEFITS

EXERTA provides:

- ◆ Superior lubrication performance and anti-wear properties
- ◆ Protect surfaces in wet operating conditions
- ◆ Superior thermal and oxidation stability
- ◆ Protection against rust and corrosion
- ◆ Effective control of foam and air release

	Technical Data*				
ISO Grades	46	68	100	150	320
Density at 15 °C	0.886	0.887	0.888	0.8863	0.904
Kinematic Viscosity mm ² /s @ 40°C	45	68	99	150	320
Viscosity Index	105	105	100	95	95
Flash Point, °C	220	230	250	260	270
Pour Point, °C	-15	-15	-15	-15	-9
Product code	227001	227002	227003	227004	227005

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.